

MSDS# 1150-02

## MATERIAL SAFETY DATA SHEET

### SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER: Universal #1150  
PRODUCT COLOR: Violet  
CHEMICAL NAME: Mixture  
FORMULA: Proprietary Mixture  
HMIS HAZARD CODE H:1 F:1 R:0

**Supplier:**

Universal Stenciling & Marking Systems, Inc. (727) 894-3027  
205 15<sup>th</sup> Ave. S.E.  
St. Petersburg, FL 33701

**Emergency Telephone Number:**

TRANSPORTATION: CHEMTREC (703) 527-3887

### SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Listed below are all the hazardous ingredients, with CAS# and hazard data, of this mixture, pursuant to NJ Admin Code Title 8, Chap 59 (NJ Worker and Community Right to Know Act) and the Special Health Hazard Substance List (NJAC 8:59-10). This exceeds Federal OSHA requirements. NJ requires that the five most predominant ingredients be listed, which may include a Trade Secret Registry Number (NJTSRN) to cover those nonhazardous top five ingredients not specifically listed. Available health hazard and physical property information concerning the mixture is furnished in this data sheet. In the event of a medical emergency, specific chemical information will be made immediately available to a treating physician or nurse.

<u>Ingredient(s)</u>	<u>CAS Number</u>	<u>Weight %</u>	<u>OSHA TLV</u>	<u>ACGIH TLV</u>
Water	7732-18-5		Not Determined	Not Determined

NJTSRN: 1150VIO

### SECTION 3. HAZARDS IDENTIFICATION

**Emergency Overview:** As noted in the preface to published values adopted by the ACGIH, TLV's represent conditions under which it is believed that nearly all workers may be repeatedly

MSDS# 1150-02

exposed day after day without adverse effect. Because of wide variation in individual susceptibility however, a small percentage of workers may experience discomfort from some substances at concentrations at or below the threshold limit; a smaller percentage may be affected more seriously by aggravation of a pre-existing condition or by development of occupational illness.

### Potential Health Effects

INGESTION: Slightly irritating to gastrointestinal tract. Can cause headache, diarrhea, drowsiness, breathing difficulties, nausea, vomiting.

EYES: Slightly irritating. May cause redness and/or blurred vision, but reversible within seven days.

SKIN: Essentially non-toxic and non-irritating.

INHALATION: Essentially non-toxic and non-irritating.

## SECTION 4. FIRST AID MEASURES

INGESTION: Currently available information does not contraindicate induction of vomiting. Induce vomiting, if conscious, as directed by medical personnel. Seek medical attention.

EYES: Flush immediately with water for at least 15 minutes. Seek medical attention.

SKIN: Minimal hazard. No significant risk to health. Seek medical attention if any adverse symptoms appear.

INHALATION: Minimal hazard. No significant risk to health. Seek medical attention if any adverse symptoms appear.

## SECTION 5. FIREFIGHTING MEASURES

FLASH POINT (°F, TCC): >200

FLAMMABLE LIMITS: LEL: N/Ap UEL: unknown  
LEL value reported is lowest listed for any ingredient in mixture.

EXTINGUISHING MEDIA: Water fog, Multipurpose foam, Dry chemical, CO2

SPECIAL FIREFIGHTING PROCEDURES:  
Fight as volatile liquid fire.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Secure area and remove all sources of ignition and heat. Prevent additional discharge of material. Absorb small spills with sand, filter-aid, vermiculite or other inert absorbent material. For large spills, prevent material from entering sewers or water courses. Contain spill with sand, or earth dikes. Recover as much as possible by pumping. Treat remainder as small spill. Dispose of waste in accordance with applicable government regulations. Wear chemical goggles, gloves, boots, and protective clothing. Wear respirator if necessary.

## SECTION 7. HANDLING AND STORAGE

STORAGE TEMPERATURE: 40 - 90° F

SHELF LIFE: Recommended use within 12 months.

HANDLING AND STORAGE PRECAUTIONS: Store in tightly closed or properly vented container away from heat, sparks, open flame, or strong oxidizing agents. Containers must be properly grounded and adequate ventilation provided. Unscrew all caps slowly. Do not unscrew entirely until all pressure has been completely released.

REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT: Handle all equipment containing liquid mixture as reported on this MSDS. Equipment with dried mixture must be handled with the same care as other dried organic coatings. All cleaning material should be handled according to their instructions and their MSDSs.

OTHER PRECAUTIONS: Use only with adequate ventilation. Dispose of empty containers promptly and properly.

SPECIAL PRECAUTIONS: None

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses must not be worn.

SKIN PROTECTION: Depending on the conditions of use, protective gloves, clothing, boots, head and face protection should be worn.

RESPIRATORY/VENTILATION: If workplace exposure limits of product or any component is exceeded, NIOSH/MSHA approved respiratory protection must be used.

ENGINEERING CONTROLS: Provide local exhaust or general room ventilation to minimize exposure to vapors.

MSDS# 1150-02

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:	Liquid
ODOR:	Low
BOILING POINT (°F):	>240
VAPOR PRESSURE (mm Hg):	<8.0
VAPOR DENSITY (Air=1):	1
SOLUBILITY IN WATER:	Complete
SPECIFIC GRAVITY (H <sub>2</sub> O=1):	1.19
% VOLATILE BY VOLUME:	15
EVAPORATION RATE (nBuAcet=1):	<0.01

## SECTION 10. REACTIVITY

STABLE:	Yes
HAZARDOUS POLYMERIZATION:	No
INCOMPATIBILITIES:	Strong oxidizing agents, strong acids, strong bases, alkali metals, halogens
DECOMPOSITION PRODUCTS:	CO, CO <sub>2</sub> , Organic Combustion Products, Oxides of Nitrogen

## SECTION 11. TOXICOLOGICAL INFORMATION

No Data Available

## SECTION 12. ECOLOGICAL INFORMATION

No Data Available

MSDS# 1150-02

**SECTION 13. DISPOSAL CONSIDERATIONS**

Consult Federal, State, and Local Regulations for accepted procedures of disposal, and any reporting or notification requirements.

**SECTION 14. TRANSPORTATION INFORMATION**

DOT SHIPPING NAME: Printing Ink  
DOT HAZARD CLASS: Not Regulated  
UN NUMBER: None  
DOT LABEL: None Required  
FREIGHT CLASS: 55

**SECTION 15. REGULATORY INFORMATION**

TSCA STATUS: Listed

OTHER REGULATORY:

<u>Ingredient(s)</u>	<u>SARA 302</u>	<u>SARA 313</u>	<u>RECRA</u>	<u>PROP 65</u>
Water	No	No	No	No
NJTSRN: 1150VIO	NO	No	No	No

**SECTION 16. OTHER INFORMATION**

REASON FOR ISSUE: MSDS form revision

PREPARED BY: Don Wright

TITLE: President

APPROVAL DATE: 05/07/2000

SUPERCEDES DATE: 01/27/1998

**DISCLAIMER OF LIABILITY**

MSDS# 1150-02

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material described in this MSDS. Information contained herein is given in good faith and believed to be true and accurate, but all statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material, or results to be obtained from the use thereof. All of the ingredients in this product that are considered to present a health hazard as defined in Appendix A of the OSHA Hazard Communication standard (29CFR 1910.1200) are listed in Section II. All of the information given, including ingredient identification, CAS Number, and quantity, is proprietary information, which has been provided in order to meet the objective of the Hazard Communication standard. This formulation information is confidential, and only to be disclosed in accordance with Federal and State safety and health regulations. Permission to disclose any ingredient information for any other purpose is neither given nor implied.